AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

Claims 1-19 (Canceled).

- 20. (Currently Amended) A process for preparing high density green compacts comprising the following steps:
- (a) providing subjecting a composition of an iron or iron-based powder, wherein less than about 5% of the iron-based powder particles have a size below 45 µm, and a lubricant added to the powder, to uniaxial compaction in a die at a compaction pressure of at least about 800 MPa; and
- (b) uniaxially compacting the powder in a die at a compaction pressure of at least about 800 MPa; and
 - (c)(b) ejecting the green body from the die.
- 21. (Previously Presented) The process of claim 20, further comprising mixing said powder with graphite and other additives.
- 22. (Previously Presented) The process of claim 20, wherein the compaction is performed in a single step.

- 23. (Currently Amended) The process of claim 20, wherein at least about 50% of the iron-based powder consists of particles having a particle size above about 106 μm.
- 24. (Currently Amended) The process of claim 20, wherein at least about 60% of the iron-based powder consists of particles having a particle size above about 106 μm.
- 25. (Currently Amended) The process of claim 20, wherein at least about 70% of the iron-based powder consists of particles having a particle size above about 106 μm.
- 26. (Currently Amended) The process of claim 20, wherein at least 50% of the iron-based powder consists of particles having a particle size above about 212 µm.
- 27. (Currently Amended) The process of claim 26, wherein at least 60% of the iron-based powder consists of particles having a particle size above about 212 μm.
- 28. (Currently Amended) The process of claim 26, wherein at least 70% of the iron-based powder consists of particles having a particle size above about 212 μm.

- 29. (Currently Amended) The process according to of claim 26, wherein the maximum particle size is about 2 mm.
- 30. (Previously Presented) The process of claim 22, wherein the graphite is present in an amount of about 0.1 to 1.0%.
- 31. (Currently Amended) The process of claim 20, wherein the iron-based powder is combined with a the lubricant in an amount between about 0.05 and about 0.6% by weight before compaction.

32-33. (Canceled)

- 34. (Currently Amended) The process of claim 20 21, wherein the additives are selected from the group consisting of alloying elements, machinability enhancing agents, hard phase materials and flow agents.
- 35. (Currently Amended) The process of claims claim 20, wherein the compaction is performed at a pressure of at least 900 MPa.
- 36. (Currently Amended) The process of claims claim 35, wherein the compaction is performed at a pressure of at least 1000 MPa.
- 37. (Currently Amended) The process of claims claim 35, wherein the compaction is performed at a pressure of at least 1100 MPa.

- 38. (Previously Presented) The process of claim 20, wherein the compaction is performed at ambient temperature.
- 39. (Previously Presented) The process of claim 20, wherein the compaction is performed at elevated temperature.
- 40. (Currently Amended) The process of claim 20, further comprising sintering in a single step at a temperature above 1100°C.

41-47. (Canceled)

- 48. (Previously Presented) The process of claim 34, wherein the alloying element is selected from the group consisting of Mn, Cu, Ni, Cr, Mo, V, Co, W, Nb, Ti, Al, P, S and B.
- 49. (New) The process of claim 20, wherein the compaction is performed without using external lubrication.
- 50. (New) The process of claim 49, wherein the powder is a wateratomized, completely alloyed steel powder.
- 51. (New) The process of claim 20, wherein the powder is a wateratomized, completely alloyed steel powder.